

# Fichier produit

HCC8 LED 8" CYLINDER DOWNLIGHT SERIES

HCC8S15D010MB-HM81520940-81WDH


COOPER LIGHTING



IP  
47

Lumens: 1,500, 2,000, 3,000, 4,000, 6,000 and 8,000, 4 color temperatures: 2700K, 3000K, 3500K, 4000K CCT; CRI: 80 or 90, Distributions: Precision-formed reflectors in Narrow, Medium and Wide, Wall wash distribution with exclusive rotatable linear spread lens, Specular, Semi-Specular and White reflectors; Black or White baffles, Cylinder colors: Matte White, Matte Black, Bronze and Silver, Universal Voltage 120V – 277V; 0-10V analog dimming down to 1%, Mounting: wall, surface, pendant and aircraft cable, L70 at 50,000 hours (70% lumen maintenance at 50,000 hours)

## Surface lumineuse 1 (intégré)



Type de source	LED	CCT	3000 K
Puissance nominative du lampe	13,9 W	CRI	100
Flux totale	1402 lm	LOR	100 %
Efficacité lumineuse	101 lm/W	Puissance totale	13,9 W

## Type de montage

Encastré dans le plafond

## Forme et dimensions

Hauteur: 10 mm

Diamètre: 216 mm

## Réglable

Rigide

## Électrique

Puissance du système: 13,9 W

## Types de protection

IP: 47